

FlowReadout™

FlowReadout™ Specifications

Power:	9 VDC alkaline battery
	Current Draw: 30 mA
Battery life:	Approximately 10 hours
	Auto turn off after 3 minutes (can be disabled)
	Low Battery Indication (below 6VDC)
Display Accuracy:	± 1 digit
Display Repeatability:	± 1 digit
Display Units:	English or Metric
Display Select:	3 Blade Turbine: .01 Gallon, .01 Liter
	6 Blade Turbine: .01 Gallon, .01 Liter
Turbine Select:	3 Blade High
	3 Blade Low
	6 Blade Low
Cumulative Flow:	.1 to 144 hours
Time Units:	.1 hour (6 minutes)

Flow Input Sensor Specifications

Pick Up Type:	Infrared
Infrared Tuning:	Automatic, Self Adjusting
Input Sample Rate:	Once per 200ms
Display Update:	1 per second
Pick Up Status:	No pick up: Blank display (--)



Part # FKR2002

Price \$610.00

Clip onto RotoFlow™, StackFlow™, StackValve™, or StackController™



© 2009 MOLDERS CHOICE, Inc.



24 Hour Service - 7 Days a week

1-800-809-4623

WebSite: www.molderschoice.com • Email: modlers@molderschoice.com