Flow Kits

FlowReadout™ Kit # **FKR-2212** **$940.00**

Easy to use, hand held FlowReadout™ in a kit. Measures flow in the following ranges using RotoFlow™ with quick connect couplings.

- 1/4" NPT, .5 to 5.2 GPM RotoFlow™ RFL-0404-C
- 3/8" NPT, 1 to 12 GPM RotoFlow™ RFH-0606-C

Operational Features:

- Digital Flow Selection
- English or Metric
- Digital Flow Correction
- Cumulative Flow
- Max/min Flow Limit (alarm)
- Analog Output
- Auto Shutdown

Comes with Instruction and Operation Manual in a handy carrying and storage case. Ready to use.

ThermoFlow™ Analyzer Kit # **FKA-2202** **$1340.00**

This kit measures flow and temperature in the following ranges:

- 1/4" NPT, .5 to 5.2 GPM RotoFlow™ RFL-0404
- 3/8" NPT, 1 to 12 GPM RotoFlow™ RFH-0606

Measures temperature ranging from 32° to 999°F for easy BTU or heat-exchange measurements using:

- Two "K" Temperature Sensor Cables
- 120/9V AC Converter and Data Output Cable
- Two 1/4" Thermocouples and Connection Cables
- Two 3/8" Thermocouples and Connection Cables

Operational features: (same feature as kit # FKR-2212 above)
Comes with Instruction and Operation Manual in a handy carrying and storage case. Ready to use.

ThermoFlow™ Analyzer Kit # **FKA-2212** **$1510.00**

This kit measures flow in the following ranges, using RotoFlow™ with quick connect couplings.

- 1/4" NPT, .5 to 5.2 GPM RotoFlow™ RFL-0404-C
- 3/8" NPT, 1 to 12 GPM RotoFlow™ RFH-0606-C

Measures temperature ranging from 32° to 999°F for easy BTU or heat exchange measurements using:

- Two "K" Temperature Sensor Cables
- 120/9V AC Converter and Data Output Cable
- Two 1/4" Thermocouples and Connection Cables
- Two 3/8" Thermocouples and Connection Cables

Operational features: (same feature as kit # FKR-2212 above)
Comes with Instruction and Operation Manual in a handy carrying and storage case. Ready to use.

© 2011 MOLDERS CHOICE, Inc.