

Liquid Circulating TEMPERATURE CONTROL SYSTEMS

3 DESIGNS AVAILABLE

- Sub Compact
- Standard Heavy-Duty Compact
- Vertical with Eye-Level Control

**3 Year Warranty
on all units**



Simple, Reliable, Accurate Controller

- Precise, auto-tune microprocessor
- Standard, commercial unit – easy to set up and troubleshoot. No special circuit boards.
- Large, dual display of set point & delivery temperature

Sturdy, Dependable, Construction

- High-quality, commercial components for years of trouble-free operation.
- Oversize cooling solenoid.
- Heavy-gauge sheet-metal cabinet has maximum ventilation to prolong component life.
- Seal Flush system extends pump seal life.

Maintenance Friendly

- Hinged access panels with quarter-turn screws provide easy access.
- Plug-in, commercial controller can be removed without disconnecting wires.
- Wiring organized and labeled for easy troubleshooting.

Powerful, Efficient Heater

- 9 kW Incoloy flange heater vertically mounted for efficient heating, easy maintenance, and minimal risk of high temperature damage.
- Insulated to minimize heat loss. Saves money and improves accuracy.

Built-In Safety Features

- Low-pressure switch and pressure relief valve.
- Internal bypass protects your heater if flow drops off.
- Overload relay on motor contactor.

High Efficiency Pump – horizontally mounted for minimum cavitation and maximum flow

© 2009 MOLDERS CHOICE, Inc.



24 Hour Service - 7 Days a week

1-800-809-4623

WebSite: www.molderschoice.com • Email: molders@molderschoice.com