

MOLDERS CHOICE NOZZLE REFERENCE GUIDE

CALL US FIRST FOR YOUR NOZZLE NEEDS!

Press Thread	Rear Opening	Thread Length
NEW BRITAIN		
4" - 6 (Female)	55 mm	3.20
44 mm - 3 mm TRAP*	30 mm	1.44
45 mm - 4 mm	12 mm	1.88
55 mm - 3 mm	.750	1.56
55 mm - 3 mm	1.26	1.56
65 mm - 3 mm TRAP*	48 mm	2.00
NIIGATA		
40 mm - 3 mm	30 mm	1.25
50 mm - 2 mm	1.35	2.02
NISSEI		
35 mm - 2 mm	20 mm	1.00
35 mm - 2 mm	20 mm	1.44
40 mm - 2 mm	20 mm	1.31
40 mm - 2 mm	20 mm	1.63
45 mm - 2 mm	1.195	1.19
50 mm - 2 mm	26 mm	1.70
50 mm - 12 T.P.I.		1.85
60 mm - 2 mm	47 mm	1.87
60 mm - 3 mm	1.000	1.50
1-3/8" - 12	.750	1.63
NEWBURY		
1-1/2' - 12	.843	1.19
REED		
1-1/4" - 8 (Buttress)	.625	1.31
1-1/2" - 12	.812	1.66
1-3/4" - 8	.750	1.75
1-3/4" - 12	.1000	1.00
2" - 12 (Female)	1.250	1.25

Press Thread	Rear Opening	Thread Length
SANDRETTO		
40 mm - 3 mm	30 mm	40 mm
50 mm - 3 mm	35 mm	55 mm
55 mm - 3 mm	40 mm	55 mm
60 mm - 3 mm	45 mm	60 mm
70 mm - 4 mm	55 mm	64 mm
SUMITOMO		
48 mm - 2 mm	32 mm	1.31
TOSHIBA		
1-1/2" - 12	15 mm	1.38
1-1/2" - 12	15 mm	1.00
3-1/4" - 8	52 mm	1.97
38 mm - 1.5 mm	15 mm	.96
48 mm - 1.5 mm	25 mm	1.62
60 mm - 4 mm	28 mm	1.62
60 mm - 4 mm	32 mm	1.61
60 mm - 4 mm	36 mm	1.62
80 mm - 4 mm	55 mm	2.94
TOYO		
36 mm - 2 mm	23 mm	1.30
42 mm - 3 mm	24 mm	1.26
50 mm - 3 mm	26 mm	2.06
65 mm - 4 mm	32 mm	1.61
65 mm - 4mm	40 mm	1.61
TRUEBLOOD		
7/8" - 12	.246	.78
1-1/4" - 12	.63	1.16
UBE		
50 mm - 2 mm	35 mm	1.42
VAN DORN (also see Demag)		
1-1/4" - 12	.750	1.63
1-3/4" - 8	1.25	1.75

© 2009 MOLDERS CHOICE, Inc.



24 Hour Service - 7 Days a week

1-800-809-4623

WebSite: www.molderschoice.com • Email: molders@molderschoice.com